



## OSLC Change Management Version 3.0. Part 3: Constraints

OASIS Standard with Approved Errata 01

06 July 2023

### This stage:

<https://docs.oasis-open-projects.org/oslc-op/cm/v3.0/errata01/os/change-mgt-shapes.html> (Authoritative)

<https://docs.oasis-open-projects.org/oslc-op/cm/v3.0/errata01/os/change-mgt-shapes.pdf>

### Previous stage:

<https://docs.oasis-open-projects.org/oslc-op/cm/v3.0/os/change-mgt-shapes.html> (Authoritative)

<https://docs.oasis-open-projects.org/oslc-op/cm/v3.0/os/change-mgt-shapes.pdf>

### Latest stage:

<https://docs.oasis-open-projects.org/oslc-op/cm/v3.0/change-mgt-shapes.html> (Authoritative)

<https://docs.oasis-open-projects.org/oslc-op/cm/v3.0/change-mgt-shapes.pdf>

### Latest version:

<https://open-services.net/spec/cm/latest>

### Latest editor's draft:

<https://open-services.net/spec/cm/latest-draft>

### Open Project:

[OASIS Open Services for Lifecycle Collaboration \(OSLC\) OP](#)

### Project Chairs:

Jim Amsden ([jamsden@us.ibm.com](mailto:jamsden@us.ibm.com)), IBM

Andrii Berezovskyi ([andriib@kth.se](mailto:andriib@kth.se)), KTH

### Editors:

Jim Amsden ([jamsden@us.ibm.com](mailto:jamsden@us.ibm.com)), IBM

Samuel Padgett ([spadgett@us.ibm.com](mailto:spadgett@us.ibm.com)), IBM

Steve Speicher ([sspeiche@us.ibm.com](mailto:sspeiche@us.ibm.com)), IBM

### Additional components:

This specification is one component of a Work Product that also includes:

- OSLC Change Management Version 3.0. Part 1: Specification. <https://docs.oasis-open-projects.org/oslc-op/cm/v3.0/errata01/os/change-mgt-spec.html>
- OSLC Change Management Version 3.0. Part 2: Vocabulary. <https://docs.oasis-open-projects.org/oslc-op/cm/v3.0/errata01/os/change-mgt-vocab.html>
- OSLC Change Management Version 3.0. Part 3: Constraints (this document). <https://docs.oasis-open-projects.org/oslc-op/cm/v3.0/errata01/os/change-mgt-shapes.html>
- OSLC Change Management Version 3.0. Part 4: Machine Readable Vocabulary Terms. <https://docs.oasis-open-projects.org/oslc-op/cm/v3.0/errata01/os/change-mgt-vocab.ttl>
- OSLC Change Management Version 3.0. Part 5: Machine Readable Constraints. <https://docs.oasis-open-projects.org/oslc-op/cm/v3.0/errata01/os/change-mgt-shapes.ttl>

### Related work:

This specification is related to:

- Open Services for Lifecycle Collaboration Change Management Specification Version 2.0. <http://open-services.net/bin/view/Main/CmSpecificationV2>

### RDF Namespaces:

## Standards Track Work Product

<http://open-services.net/ns/cm#>

### Abstract:

This document includes approved errata, as described in OSLC Change Management Version 3.0. Part 1: Specification, Appendix C. Errata.

OSLC Change Management Version 3.0. Part 2: Vocabulary defines the OSLC Change Management RDF vocabulary terms and resources. This document specifies the standard constraints on those vocabulary terms using OSLC ResourceShapes.

### Status:

This document was last revised or approved by the membership of OASIS on the above date. The level of approval is also listed above. Check the "Latest stage" location noted above for possible later revisions of this document. Any other numbered Versions and other technical work produced by the Open Project are listed at <https://github.com/oslc-op/oslc-specs>.

Comments on this work can be provided by opening issues in the project repository or by sending email to the project's public comment list [oslc-op@lists.oasis-open-projects.org](mailto:oslc-op@lists.oasis-open-projects.org).

The English version of this specification is the only normative version. Non-normative translations may also be available. Note that any machine-readable content ([Computer Language Definitions](#)) declared Normative for this Work Product is provided in separate plain text files. In the event of a discrepancy between any such plain text file and display content in the Work Product's prose narrative document(s), the content in the separate plain text file prevails.

### Citation format:

When referencing this specification the following citation format should be used:

#### **[OSLC-CM-3.0-Part3]**

*OSLC Change Management Version 3.0. Part 3: Constraints*. Edited by Jim Amsden, Samuel Padgett, and Steve Speicher. 06 July 2023. OASIS Standard with Approved Errata 01. <https://docs.oasis-open-projects.org/oslc-op/cm/v3.0/errata01/os/change-mgt-shapes.html>.

Latest stage: <https://docs.oasis-open-projects.org/oslc-op/cm/v3.0/change-mgt-shapes.html>.

### Notices

Copyright © OASIS Open 2023. All Rights Reserved.

All capitalized terms in the following text have the meanings assigned to them in the OASIS Intellectual Property Rights Policy (the "OASIS IPR Policy"). The full [Policy](#) may be found at the OASIS website.

This specification is published under the [Attribution 4.0 International \(CC BY 4.0\)](#). Portions of this specification are also provided under the [Apache License 2.0](#).

All contributions made to this project have been made under the [OASIS Contributor License Agreement \(CLA\)](#).

For information on whether any patents have been disclosed that may be essential to implementing this specification, and any offers of patent licensing terms, please refer to the [Open Projects IPR Statements page](#).

This document and translations of it may be copied and furnished to others, and derivative works that comment on or otherwise explain it or assist in its implementation may be prepared, copied, published, and distributed, in whole or in part, without restriction of any kind, provided that the above copyright notice and this section are included on all such copies and derivative works. However, this document itself may not be modified in any way, including by removing the copyright notice or references to OASIS, except as needed for the purpose of developing any document or deliverable produced by an OASIS Open Project or OASIS Technical Committee (in which case the rules applicable to copyrights, as set forth in the OASIS IPR Policy, must be followed) or as required to translate it into languages other than English.

The limited permissions granted above are perpetual and will not be revoked by OASIS or its successors or assigns.

This document and the information contained herein is provided on an "AS IS" basis and OASIS DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE INFORMATION HEREIN WILL NOT INFRINGE ANY OWNERSHIP RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

OASIS requests that any OASIS Party or any other party that believes it has patent claims that would necessarily be infringed by implementations of this OASIS Project Specification or OASIS Standard, to notify the OASIS TC Administrator and provide an indication of its willingness to grant patent licenses to such patent claims in a manner consistent with the IPR Mode of the OASIS Technical Committee that produced this specification.

OASIS invites any party to contact the OASIS TC Administrator if it is aware of a claim of ownership of any patent claims that would necessarily be infringed by implementations of this specification by a patent holder that is not willing to provide a license to such patent claims in a manner consistent with the IPR Mode of the OASIS Open Project that produced this specification. OASIS may include such claims on its website, but disclaims any obligation to do so.

OASIS takes no position regarding the validity or scope of any intellectual property or other rights that might be claimed to pertain to the implementation or use of the technology described in this document or the extent to which any license under such rights might or might not be available; neither does it represent that it has made any effort to identify any such rights. Information on OASIS' procedures with respect to rights in any document or deliverable produced by an OASIS Technical Committee can be found on the OASIS website. Copies of claims of rights made available for publication and any assurances of licenses to be made available, or the result of an attempt made to obtain a general license or permission for the use of such proprietary rights by implementers or users of this OASIS Open Project Specification or OASIS Standard, can be obtained from the OASIS TC Administrator. OASIS makes no representation that any information or list of intellectual property rights will at any time be complete, or that any claims in such list are, in fact, Essential Claims.

The name "OASIS" is a trademark of [OASIS](#), the owner and developer of this specification, and should be used only to refer to the organization and its official outputs. OASIS welcomes reference to, and implementation and use of, specifications, while reserving the right to enforce its marks against misleading uses. Please see <https://www.oasis-open.org/policies-guidelines/trademark/> for above guidance.

## Table of Contents

- 1. [Introduction](#)
  - 1.1 [Terminology](#)
  - 1.2 [References](#)
  - 1.3 [Typographical Conventions and Use of RFC Terms](#)
- 2. [Change Management Resource Constraints](#)
  - 2.1 [Resource: ChangeRequest](#)
  - 2.2 [Resource: ChangeNotice](#)
  - 2.3 [Resource: Defect](#)
  - 2.4 [Resource: Enhancement](#)
  - 2.5 [Resource: ReviewTask](#)
  - 2.6 [Resource: Task](#)
- 3. [Conformance](#)

## 1. Introduction

*This section is non-normative.*

RDF vocabularies define the terms and resources for a domain of interest, life-cycle management in the case of OSLC Change Management. These vocabularies are often specified in an open manner, without providing information such as property domain and range assertions, cardinalities, etc. This helps keep the vocabulary applicable for a wide range of uses and furthering integration with other vocabularies.

However, it is often desirable to closed down a vocabulary with specific constraints to facilitate using the vocabulary for a specific purpose. This document specifies the constraints for using the OSLC Change Management vocabulary in OSLC. Different sets of constraints may be applied to a vocabulary in order to tailor its use, without overly constraining the vocabulary for other usages.

These constraints apply to the core vocabulary defined in [OSLC Change Management Version 3.0. Part 2: Vocabulary](#).




Fig. 1 OSLC Change Management 3.0 Overview

### 1.1 Terminology

Terminology is based on OSLC Core Overview [OSLCCore3], W3C Linked Data Platform [LDP], W3C's Architecture of the World Wide Web [WEBARCH], Hyper-text Transfer Protocol [HTTP11].

### 1.2 References

#### 1.2.1 Normative references

[HTTP11]

R. Fielding, Ed.; J. Reschke, Ed.. *Hypertext Transfer Protocol (HTTP/1.1): Message Syntax and Routing*. IETF, June 2014. Proposed Standard. URL: <https://httpwg.org/specs/rfc7230.html>

[LDP]

Steve Speicher; John Arwe; Ashok Malhotra. *Linked Data Platform 1.0*. W3C, 26 February 2015. W3C Recommendation. URL: <https://www.w3.org/TR/ldp/>

[OSLCCore3]

Steve Speicher; Jim Amsden. *OSLC Core Overview v3.0*. OASIS. Project Specification. URL: <https://docs.oasis-open-projects.org/oslc-op/core/v3.0/oslc-core.html>

[RFC2119]

S. Bradner. *Key words for use in RFCs to Indicate Requirement Levels*. IETF, March 1997. Best Current Practice. URL: <https://www.rfc-editor.org/rfc/rfc2119>

[RFC8174]

B. Leiba. *Ambiguity of Uppercase vs Lowercase in RFC 2119 Key Words*. IETF, May 2017. Best Current Practice. URL: <https://www.rfc-editor.org/rfc/rfc8174>

## 1.2.2 Informative references

[OSLCQM]

Paul McMahan. [Open Services for Lifecycle Collaboration Quality Management Specification Version 2.0](http://open-services.net/bin/view/Main/QmSpecificationV2). <http://open-services.net>. Final. URL: <http://open-services.net/bin/view/Main/QmSpecificationV2>

[OSLCRM]

Ian Green. [Open Services for Lifecycle Collaboration Requirements Management Specification Version 2.0](http://open-services.net/bin/view/Main/RmSpecificationV2). <http://open-services.net>. Final. URL: <http://open-services.net/bin/view/Main/RmSpecificationV2>

[WEBARCH]

Ian Jacobs; Norman Walsh. [Architecture of the World Wide Web, Volume One](https://www.w3.org/TR/webarch/). W3C, 15 December 2004. W3C Recommendation. URL: <https://www.w3.org/TR/webarch/>

## 1.3 Typographical Conventions and Use of RFC Terms

As well as sections marked as non-normative, all authoring guidelines, diagrams, examples, and notes in this specification are non-normative. Everything else in this specification is normative.

The key words "**MUST**", "**MUST NOT**", "**REQUIRED**", "**SHALL**", "**SHALL NOT**", "**SHOULD**", "**SHOULD NOT**", "**RECOMMENDED**", "**NOT RECOMMENDED**", "**MAY**", and "**OPTIONAL**" in this specification are to be interpreted as described in [BCP 14 \[RFC2119\]](#) [\[RFC8174\]](#) when, and only when, they appear in all capitals, as shown here.

In addition to the namespace URLs and namespace prefixes `oslc`, `rdf`, `dcterms` and `foaf` defined in the [OSLC Core specification](#), OSLC CM defines the namespace URI of `http://open-services.net/ns/cm#` with a namespace prefix of `oslc_cm`

This specification also uses these namespace prefix definitions:

- `oslc_rm` : `http://open-services.net/ns/rm#` [\[OSLCRM\]](#)
- `oslc_qm` : `http://open-services.net/ns/qm#` [\[OSLCQM\]](#)

## 2. Change Management Resource Constraints

Property value types that are not defined in the following sections, are defined in [OSLC Core - Defining OSLC Properties](#)

Naming convention for relationship properties follows this pattern:

- **related** - Identifies a loose relationship between a Change Request and referenced resource. These relationships can be used to name associated resources managed by other service providers.
- **tracks** - Identifies that a Change Request is used to track the lifecycle of referenced resource. From the CM tool perspective, these relationships can be used to track work that needs to be done for referenced resources.
- **affects** - Indicates that the Change Request affects, or has been predetermined to have impact on, the related resource. These property relationships can be used to understand the potential impact of referenced resources.

### 2.1 Resource: ChangeRequest

The Change Request resource properties are not limited to the ones defined in this specification, service providers may provide additional properties. It is recommended that any additional properties exist in their own unique namespace and not use the namespaces defined in these specifications.

- **Describes:** <http://open-services.net/ns/cm#ChangeRequest>
- **Summary:** A general type for records in a Change Management.

#### ChangeRequest Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>dcterms:contributor</code>	Zero-or-many	unspecified	AnyResource	Either	<code>oslc:Any</code>	The person(s) who are responsible for the work needed to complete the change request (reference: Dublin Core). It is likely that the target resource will be a <code>foaf:Person</code> but that is not necessarily the case.
<code>dcterms:created</code>	Zero-or-one	true	dateTime	N/A	Unspecified	Timestamp of resource creation (reference: Dublin Core).
<code>dcterms:creator</code>	Zero-or-many	unspecified	AnyResource	Either	<code>oslc:Any</code>	Creator or creators of resource (reference: Dublin Core). It is likely that the target resource will be a <code>foaf:Person</code> but that is not necessarily the case.
<code>dcterms:description</code>	Zero-or-one	unspecified	XMLLiteral	N/A	Unspecified	Descriptive text (reference: Dublin Core) about resource represented as rich text in XHTML content. <b>SHOULD</b> include only content that is valid and suitable inside an XHTML <div> element.
<code>dcterms:identifier</code>	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Assigned by the service provider when a resource is created. Not intended for end-user display.
<code>dcterms:modified</code>	Zero-or-one	true	dateTime	N/A	Unspecified	Timestamp of latest resource modification (reference: Dublin Core).
<code>dcterms:subject</code>	Zero-or-many	unspecified	string	N/A	Unspecified	Tag or keyword for a resource. Each occurrence of a <code>dcterms:subject</code> property denotes an additional tag for the resource.

## Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>dcterms:title</code>	Exactly-one	unspecified	XMLLiteral	N/A	Unspecified	Title (reference: Dublin Core) or often a single line summary of the resource represented as rich text in XHTML content. <b>SHOULD</b> include only content that is valid and suitable inside an XHTML <div> element.
<code>oslc_cm:affectedByDefect</code>	Zero-or-many	unspecified	Resource	Reference	<code>oslc_cm:Defect</code>	Change request is affected by a reported defect. It is likely that the target resource will be an <code>oslc_cm:Defect</code> but that is not necessarily the case.
<code>oslc_cm:affectsPlanItem</code>	Zero-or-many	unspecified	Resource	Reference	Unspecified	Change request affects plan item.
<code>oslc_cm:affectsRequirement</code>	Zero-or-many	unspecified	Resource	Reference	<code>oslc_rm:Requirement</code>	Change request affecting a Requirement. It is likely that the target resource will be an <code>oslc_rm:Requirement</code> but that is not necessarily the case.
<code>oslc_cm:affectsTestResult</code>	Zero-or-many	unspecified	Resource	Reference	<code>oslc_config:ChangeSet</code>	Associated QM resource that is affected by this Change Request. It is likely that the target resource will be an <code>oslc_qm:TestResult</code> but that is not necessarily the case.
<code>oslc_cm:approved</code>	Zero-or-one	unspecified	boolean	N/A	Unspecified	Whether or not the Change Request has been approved.
<code>oslc_cm:authorizer</code>	Zero-or-many	unspecified	AnyResource	Either	<code>foaf:Agent</code>	Agents who are responsible authorizing and/or has authorized effort to be expended to address a set of child change requests.
<code>oslc_cm:blocksTestExecutionRecord</code>	Zero-or-many	unspecified	Resource	Reference	<code>oslc_config:ChangeSet</code>	Associated QM resource that is blocked by this Change Request. It is likely that the target resource will be an <code>oslc_qm:TestExecutionRecord</code> but that is not necessarily the case.
<code>oslc_cm:closed</code>	Zero-or-one	unspecified	boolean	N/A	Unspecified	Whether or not the Change Request is completely done, no further fixes or fix verification is needed.
<code>oslc_cm:closeDate</code>	Zero-or-one	true	dateTime	N/A	Unspecified	The date at which no further activity or work is intended to be conducted.
<code>oslc_cm:fixed</code>	Zero-or-one	unspecified	boolean	N/A	Unspecified	Whether or not the Change Request has been fixed.
<code>oslc_cm:implementsRequirement</code>	Zero-or-many	unspecified	Resource	Reference	<code>oslc_rm:Requirement</code>	Implements associated Requirement. It is likely that the target resource will be an <code>oslc_rm:Requirement</code> but that is not necessarily the case.
<code>oslc_cm:inProgress</code>	Zero-or-one	unspecified	boolean	N/A	Unspecified	Whether or not the Change Request in a state indicating that active work is occurring. If <code>oslc_cm:inProgress</code> is true, then <code>oslc_cm:fixed</code> and <code>oslc_cm:closed</code> must also be false.
<code>oslc_cm:parent</code>	Zero-or-many	unspecified	AnyResource	Either	<code>oslc_cm:ChangeRequest</code>	The related parent change requests of the subject change request. Establishes a parent/child relationship between change requests.



## Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_cm:priority</code>	Zero-or-many	unspecified	AnyResource	Either	<code>oslc_cm:Priority</code>	Priority of this change request.
<code>oslc_cm:relatedChangeRequest</code>	Zero-or-many	unspecified	Resource	Reference	Unspecified	This relationship is loosely coupled and has no specific meaning.
<code>oslc_cm:relatedTestCase</code>	Zero-or-many	unspecified	Resource	Reference	<code>oslc_config:ChangeSet</code>	Related QM test case resource. It is likely that the target resource will be an <code>oslc_qm:TestCase</code> but that is not necessarily the case.
<code>oslc_cm:relatedTestExecutionRecord</code>	Zero-or-many	unspecified	Resource	Reference	<code>oslc_config:ChangeSet</code>	Related to a QM test execution resource. It is likely that the target resource will be an <code>oslc_qm:TestExecutionRecord</code> but that is not necessarily the case.
<code>oslc_cm:relatedTestPlan</code>	Zero-or-many	unspecified	Resource	Reference	<code>oslc_config:ChangeSet</code>	Related QM test plan resource. It is likely that the target resource will be an <code>oslc_qm:TestPlan</code> but that is not necessarily the case.
<code>oslc_cm:relatedTestScript</code>	Zero-or-many	unspecified	Resource	Reference	<code>oslc_config:ChangeSet</code>	Related QM test script resource. It is likely that the target resource will be an <code>oslc_qm:TestScript</code> but that is not necessarily the case.
<code>oslc_cm:reviewed</code>	Zero-or-one	unspecified	boolean	N/A	Unspecified	Whether or not the Change Request has been reviewed.
<code>oslc_cm:state</code>	Zero-or-one	unspecified	unspecified	Either	<code>oslc_cm:State</code>	Used to indicate the state of the change request. This property is often read-only, but could be changed using OSLC Actions.
<code>oslc_cm:status</code>	Zero-or-one	unspecified	string	N/A	Unspecified	Used to indicate the status of the change request. This property is often read-only.
<code>oslc_cm:testedByTestCase</code>	Zero-or-many	unspecified	Resource	Reference	<code>oslc_config:ChangeSet</code>	Test case by which this change request is tested. It is likely that the target resource will be an <code>oslc_qm:TestCase</code> but that is not necessarily the case.
<code>oslc_cm:tracksChangeSet</code>	Zero-or-many	unspecified	Resource	Reference	<code>oslc_config:ChangeSet</code>	Tracks a resource that represents a set of changes on the resource.
<code>oslc_cm:tracksRequirement</code>	Zero-or-many	unspecified	Resource	Reference	<code>oslc_rm:Requirement</code>	Tracks the associated Requirement or Requirement ChangeSet resources. It is likely that the target resource will be an <code>oslc_rm:Requirement</code> but that is not necessarily the case.
<code>oslc_cm:verified</code>	Zero-or-one	unspecified	boolean	N/A	Unspecified	Whether or not the resolution or fix of the Change Request has been verified.
<code>oslc:discussedBy</code>	Zero-or-one	unspecified	AnyResource	Either	<code>oslc:Discussion</code>	A series of notes and comments about this change request.
<code>oslc:instanceShape</code>	Zero-or-many	unspecified	Resource	Reference	<code>oslc:ResourceShape</code>	Resource Shape that provides hints as to resource property value-types and allowed values.

## Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc:serviceProvider</code>	Zero-or-many	unspecified	Resource	Reference	<code>oslc:ServiceProvider</code>	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
<code>oslc:shortTitle</code>	Zero-or-one	unspecified	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. <b>SHOULD</b> include only content that is valid inside an XHTML <code>&lt;span&gt;</code> element.
<code>rdf:type</code>	Zero-or-many	unspecified	Resource	Reference	Unspecified	The resource type URIs, at least one of which should be <code>oslc_cm:ChangeRequest</code> .

### 2.2 Resource: ChangeNotice

- **Describes:** <http://open-services.net/ns/cm#ChangeNotice>
- **Summary:** A notification of a change request that requires authorization to address.
- **Description:** Represents an assignment notification of a change request. May be used also to bestow authority onto the assigned user to effect the changes.

#### ChangeNotice Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>dcterms:contributor</code>	Zero-or-many	unspecified	AnyResource	Either	<code>oslc:Any</code>	The person(s) who are responsible for the work needed to complete the change request (reference: Dublin Core). It is likely that the target resource will be a <code>foaf:Person</code> but that is not necessarily the case.
<code>dcterms:created</code>	Zero-or-one	true	dateTime	N/A	Unspecified	Timestamp of resource creation (reference: Dublin Core).
<code>dcterms:creator</code>	Zero-or-many	unspecified	AnyResource	Either	<code>oslc:Any</code>	Creator or creators of resource (reference: Dublin Core). It is likely that the target resource will be a <code>foaf:Person</code> but that is not necessarily the case.
<code>dcterms:description</code>	Zero-or-one	unspecified	XMLLiteral	N/A	Unspecified	Descriptive text (reference: Dublin Core) about resource represented as rich text in XHTML content. <b>SHOULD</b> include only content that is valid and suitable inside an XHTML <code>&lt;div&gt;</code> element.
<code>dcterms:identifier</code>	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Assigned by the service provider when a resource is created. Not intended for end-user display.
<code>dcterms:modified</code>	Zero-or-one	true	dateTime	N/A	Unspecified	Timestamp of latest resource modification (reference: Dublin Core).
<code>dcterms:subject</code>	Zero-or-many	unspecified	string	N/A	Unspecified	Tag or keyword for a resource. Each occurrence of a <code>dcterms:subject</code> property denotes an additional tag for the resource.
<code>dcterms:title</code>	Exactly-one	unspecified	XMLLiteral	N/A	Unspecified	Title (reference: Dublin Core) or often a single line summary of the resource represented as rich text in XHTML content. <b>SHOULD</b> include only content that is valid and suitable inside an XHTML <code>&lt;div&gt;</code> element.

## Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_cm:affectedByDefect</code>	Zero-or-many	unspecified	Resource	Reference	<code>oslc_cm:Defect</code>	Change request is affected by a reported defect. It is likely that the target resource will be an <code>oslc_cm:Defect</code> but that is not necessarily the case.
<code>oslc_cm:affectsPlanItem</code>	Zero-or-many	unspecified	Resource	Reference	Unspecified	Change request affects plan item.
<code>oslc_cm:affectsRequirement</code>	Zero-or-many	unspecified	Resource	Reference	<code>oslc_rm:Requirement</code>	Change request affecting a Requirement. It is likely that the target resource will be an <code>oslc_rm:Requirement</code> but that is not necessarily the case.
<code>oslc_cm:approved</code>	Zero-or-one	unspecified	boolean	N/A	Unspecified	Whether or not the Change Request has been approved.
<code>oslc_cm:authorizer</code>	Zero-or-many	unspecified	AnyResource	Either	<code>foaf:Agent</code>	Agents who are responsible authorizing and/or has authorized effort to be expended to address a set of child change requests.
<code>oslc_cm:closed</code>	Zero-or-one	unspecified	boolean	N/A	Unspecified	Whether or not the Change Request is completely done, no further fixes or fix verification is needed.
<code>oslc_cm:closeDate</code>	Zero-or-one	true	dateTime	N/A	Unspecified	The date at which no further activity or work is intended to be conducted.
<code>oslc_cm:fixed</code>	Zero-or-one	unspecified	boolean	N/A	Unspecified	Whether or not the Change Request has been fixed.
<code>oslc_cm:inProgress</code>	Zero-or-one	unspecified	boolean	N/A	Unspecified	Whether or not the Change Request is in a state indicating that active work is occurring. If <code>oslc_cm:inProgress</code> is true, then <code>oslc_cm:fixed</code> and <code>oslc_cm:closed</code> must also be false.
<code>oslc_cm:parent</code>	Zero-or-many	unspecified	AnyResource	Either	<code>oslc_cm:ChangeRequest</code>	The related parent change requests of the subject change request. Establishes a parent/child relationship between change requests.
<code>oslc_cm:priority</code>	Zero-or-many	unspecified	AnyResource	Either	<code>oslc_cm:Priority</code>	Priority of this change request.
<code>oslc_cm:relatedChangeRequest</code>	Zero-or-many	unspecified	Resource	Reference	Unspecified	This relationship is loosely coupled and has no specific meaning.
<code>oslc_cm:reviewed</code>	Zero-or-one	unspecified	boolean	N/A	Unspecified	Whether or not the Change Request has been reviewed.
<code>oslc_cm:severity</code>	Zero-or-many	unspecified	AnyResource	Either	<code>oslc_cm:Severity</code>	Severity or criticality of this change request.
<code>oslc_cm:state</code>	Zero-or-one	unspecified	unspecified	Either	<code>oslc_cm:State</code>	Used to indicate the state of the change request. This property is often read-only, but could be changed using OSLC Actions.
<code>oslc_cm:status</code>	Zero-or-one	unspecified	string	N/A	Unspecified	Used to indicate the status of the change request. This property is often read-only.
<code>oslc_cm:tracksChangeSet</code>	Zero-or-many	unspecified	Resource	Reference	<code>oslc_config:ChangeSet</code>	Tracks a resource that represents a set of changes on the resource.
<code>oslc_cm:verified</code>	Zero-or-one	unspecified	boolean	N/A	Unspecified	Whether or not the resolution or fix of the Change Request has been verified.
<code>oslc:discussedBy</code>	Zero-or-one	unspecified	AnyResource	Either	<code>oslc:Discussion</code>	A series of notes and comments about this change request.

## Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc:instanceShape</code>	Zero-or-many	unspecified	Resource	Reference	<code>oslc:ResourceShape</code>	Resource Shape that provides hints as to resource property value-types and allowed values.
<code>oslc:serviceProvider</code>	Zero-or-many	unspecified	Resource	Reference	<code>oslc:ServiceProvider</code>	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
<code>oslc:shortTitle</code>	Zero-or-one	unspecified	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. <b>SHOULD</b> include only content that is valid inside an XHTML <code>&lt;span&gt;</code> element.
<code>rdf:type</code>	Zero-or-many	unspecified	Resource	Reference	Unspecified	The resource type URIs, at least one of which should be <code>oslc_cm:ChangeRequest</code> .

### 2.3 Resource: Defect

A software or product defect. Used by Quality Management tools to report defects in testing.

- **Describes:** <http://open-services.net/ns/cm#Defect>
- **Summary:** A software or product defect.
- **Description:** Used to report defects in testing.

#### Defect Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>dcterms:contributor</code>	Zero-or-many	unspecified	AnyResource	Either	<code>oslc:Any</code>	The person(s) who are responsible for the work needed to complete the change request (reference: Dublin Core). It is likely that the target resource will be a <code>foaf:Person</code> but that is not necessarily the case.
<code>dcterms:created</code>	Zero-or-one	true	dateTime	N/A	Unspecified	Timestamp of resource creation (reference: Dublin Core).
<code>dcterms:creator</code>	Zero-or-many	unspecified	AnyResource	Either	<code>oslc:Any</code>	Creator or creators of resource (reference: Dublin Core). It is likely that the target resource will be a <code>foaf:Person</code> but that is not necessarily the case.
<code>dcterms:description</code>	Zero-or-one	unspecified	XMLLiteral	N/A	Unspecified	Descriptive text (reference: Dublin Core) about resource represented as rich text in XHTML content. <b>SHOULD</b> include only content that is valid and suitable inside an XHTML <code>&lt;div&gt;</code> element.
<code>dcterms:identifier</code>	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Assigned by the service provider when a resource is created. Not intended for end-user display.
<code>dcterms:modified</code>	Zero-or-one	true	dateTime	N/A	Unspecified	Timestamp of latest resource modification (reference: Dublin Core).

## Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>dcterms:subject</code>	Zero-or-many	unspecified	string	N/A	Unspecified	Tag or keyword for a resource. Each occurrence of a <code>dcterms:subject</code> property denotes an additional tag for the resource.
<code>dcterms:title</code>	Exactly-one	unspecified	XMLLiteral	N/A	Unspecified	Title (reference: Dublin Core) or often a single line summary of the resource represented as rich text in XHTML content. <b>SHOULD</b> include only content that is valid and suitable inside an XHTML <code>&lt;div&gt;</code> element.
<code>oslc_cm:affectedByDefect</code>	Zero-or-many	unspecified	Resource	Reference	<code>oslc_cm:Defect</code>	Change request is affected by a reported defect. It is likely that the target resource will be an <code>oslc_cm:Defect</code> but that is not necessarily the case.
<code>oslc_cm:affectsPlanItem</code>	Zero-or-many	unspecified	Resource	Reference	Unspecified	Change request affects plan item.
<code>oslc_cm:affectsRequirement</code>	Zero-or-many	unspecified	Resource	Reference	<code>oslc_rm:Requirement</code>	Change request affecting a Requirement. It is likely that the target resource will be an <code>oslc_rm:Requirement</code> but that is not necessarily the case.
<code>oslc_cm:affectsTestResult</code>	Zero-or-many	unspecified	Resource	Reference	<code>oslc_config:ChangeSet</code>	Associated QM resource that is affected by this Change Request. It is likely that the target resource will be an <code>oslc_qm:TestResult</code> but that is not necessarily the case.
<code>oslc_cm:approved</code>	Zero-or-one	unspecified	boolean	N/A	Unspecified	Whether or not the Change Request has been approved.
<code>oslc_cm:authorizer</code>	Zero-or-many	unspecified	AnyResource	Either	<code>foaf:Agent</code>	Agents who are responsible authorizing and/or has authorized effort to be expended to address a set of child change requests.
<code>oslc_cm:blocksTestExecutionRecord</code>	Zero-or-many	unspecified	Resource	Reference	<code>oslc_config:ChangeSet</code>	Associated QM resource that is blocked by this Change Request. It is likely that the target resource will be an <code>oslc_qm:TestExecutionRecord</code> but that is not necessarily the case.
<code>oslc_cm:closed</code>	Zero-or-one	unspecified	boolean	N/A	Unspecified	Whether or not the Change Request is completely done, no further fixes or fix verification is needed.
<code>oslc_cm:closeDate</code>	Zero-or-one	true	dateTime	N/A	Unspecified	The date at which no further activity or work is intended to be conducted.
<code>oslc_cm:fixed</code>	Zero-or-one	unspecified	boolean	N/A	Unspecified	Whether or not the Change Request has been fixed.
<code>oslc_cm:inProgress</code>	Zero-or-one	unspecified	boolean	N/A	Unspecified	Whether or not the Change Request in a state indicating that active work is occurring. If <code>oslc_cm:inProgress</code> is true, then <code>oslc_cm:fixed</code> and <code>oslc_cm:closed</code> must also be false.
<code>oslc_cm:parent</code>	Zero-or-many	unspecified	AnyResource	Either	<code>oslc_cm:ChangeRequest</code>	The related parent change requests of the subject change request. Establishes a parent/child relationship between change requests.

## Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_cm:priority</code>	Zero-or-many	unspecified	AnyResource	Either	<code>oslc_cm:Priority</code>	Priority of this change request.
<code>oslc_cm:relatedChangeRequest</code>	Zero-or-many	unspecified	Resource	Reference	Unspecified	This relationship is loosely coupled and has no specific meaning.
<code>oslc_cm:relatedTestCase</code>	Zero-or-many	unspecified	Resource	Reference	<code>oslc_config:ChangeSet</code>	Related QM test case resource. It is likely that the target resource will be an <code>oslc_qm:TestCase</code> but that is not necessarily the case.
<code>oslc_cm:relatedTestExecutionRecord</code>	Zero-or-many	unspecified	Resource	Reference	<code>oslc_config:ChangeSet</code>	Related to a QM test execution resource. It is likely that the target resource will be an <code>oslc_qm:TestExecutionRecord</code> but that is not necessarily the case.
<code>oslc_cm:relatedTestPlan</code>	Zero-or-many	unspecified	Resource	Reference	<code>oslc_config:ChangeSet</code>	Related QM test plan resource. It is likely that the target resource will be an <code>oslc_qm:TestPlan</code> but that is not necessarily the case.
<code>oslc_cm:relatedTestScript</code>	Zero-or-many	unspecified	Resource	Reference	<code>oslc_config:ChangeSet</code>	Related QM test script resource. It is likely that the target resource will be an <code>oslc_qm:TestScript</code> but that is not necessarily the case.
<code>oslc_cm:reviewed</code>	Zero-or-one	unspecified	boolean	N/A	Unspecified	Whether or not the Change Request has been reviewed.
<code>oslc_cm:severity</code>	Zero-or-many	unspecified	AnyResource	Either	<code>oslc_cm:Severity</code>	Severity or criticality of this change request.
<code>oslc_cm:state</code>	Zero-or-one	unspecified	unspecified	Either	<code>oslc_cm:State</code>	Used to indicate the state of the change request. This property is often read-only, but could be changed using OSLC Actions.
<code>oslc_cm:status</code>	Zero-or-one	unspecified	string	N/A	Unspecified	Used to indicate the status of the change request. This property is often read-only.
<code>oslc_cm:testedByTestCase</code>	Zero-or-many	unspecified	Resource	Reference	<code>oslc_config:ChangeSet</code>	Test case by which this change request is tested. It is likely that the target resource will be an <code>oslc_qm:TestCase</code> but that is not necessarily the case.
<code>oslc_cm:tracksChangeSet</code>	Zero-or-many	unspecified	Resource	Reference	<code>oslc_config:ChangeSet</code>	Tracks a resource that represents a set of changes on the resource.
<code>oslc_cm:verified</code>	Zero-or-one	unspecified	boolean	N/A	Unspecified	Whether or not the resolution or fix of the Change Request has been verified.
<code>oslc:discussedBy</code>	Zero-or-one	unspecified	AnyResource	Either	<code>oslc:Discussion</code>	A series of notes and comments about this change request.
<code>oslc:instanceShape</code>	Zero-or-many	unspecified	Resource	Reference	<code>oslc:ResourceShape</code>	Resource Shape that provides hints as to resource property value-types and allowed values.

## Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc:serviceProvider</code>	Zero-or-many	unspecified	Resource	Reference	<code>oslc:ServiceProvider</code>	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
<code>oslc:shortTitle</code>	Zero-or-one	unspecified	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. <b>SHOULD</b> include only content that is valid inside an XHTML <code>&lt;span&gt;</code> element.
<code>rdf:type</code>	Zero-or-many	unspecified	Resource	Reference	Unspecified	The resource type URIs, at least one of which should be <code>oslc_cm:ChangeRequest</code> .

### 2.4 Resource: Enhancement

- **Describes:** <http://open-services.net/ns/cm#Enhancement>
- **Summary:** A request for new functionality.

#### Enhancement Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>dcterms:contributor</code>	Zero-or-many	unspecified	AnyResource	Either	<code>oslc:Any</code>	The person(s) who are responsible for the work needed to complete the change request (reference: Dublin Core). It is likely that the target resource will be a <code>foaf:Person</code> but that is not necessarily the case.
<code>dcterms:created</code>	Zero-or-one	true	dateTime	N/A	Unspecified	Timestamp of resource creation (reference: Dublin Core).
<code>dcterms:creator</code>	Zero-or-many	unspecified	AnyResource	Either	<code>oslc:Any</code>	Creator or creators of resource (reference: Dublin Core). It is likely that the target resource will be a <code>foaf:Person</code> but that is not necessarily the case.
<code>dcterms:description</code>	Zero-or-one	unspecified	XMLLiteral	N/A	Unspecified	Descriptive text (reference: Dublin Core) about resource represented as rich text in XHTML content. <b>SHOULD</b> include only content that is valid and suitable inside an XHTML <code>&lt;div&gt;</code> element.
<code>dcterms:identifier</code>	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Assigned by the service provider when a resource is created. Not intended for end-user display.
<code>dcterms:modified</code>	Zero-or-one	true	dateTime	N/A	Unspecified	Timestamp of latest resource modification (reference: Dublin Core).
<code>dcterms:subject</code>	Zero-or-many	unspecified	string	N/A	Unspecified	Tag or keyword for a resource. Each occurrence of a <code>dcterms:subject</code> property denotes an additional tag for the resource.

## Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>dcterms:title</code>	Exactly-one	unspecified	XMLLiteral	N/A	Unspecified	Title (reference: Dublin Core) or often a single line summary of the resource represented as rich text in XHTML content. <b>SHOULD</b> include only content that is valid and suitable inside an XHTML <div> element.
<code>oslc_cm:affectedByDefect</code>	Zero-or-many	unspecified	Resource	Reference	<code>oslc_cm:Defect</code>	Change request is affected by a reported defect. It is likely that the target resource will be an <code>oslc_cm:Defect</code> but that is not necessarily the case.
<code>oslc_cm:affectsPlanItem</code>	Zero-or-many	unspecified	Resource	Reference	Unspecified	Change request affects plan item.
<code>oslc_cm:affectsRequirement</code>	Zero-or-many	unspecified	Resource	Reference	<code>oslc_rm:Requirement</code>	Change request affecting a Requirement. It is likely that the target resource will be an <code>oslc_rm:Requirement</code> but that is not necessarily the case.
<code>oslc_cm:affectsTestResult</code>	Zero-or-many	unspecified	Resource	Reference	<code>oslc_config:ChangeSet</code>	Associated QM resource that is affected by this Change Request. It is likely that the target resource will be an <code>oslc_qm:TestResult</code> but that is not necessarily the case.
<code>oslc_cm:approved</code>	Zero-or-one	unspecified	boolean	N/A	Unspecified	Whether or not the Change Request has been approved.
<code>oslc_cm:authorizer</code>	Zero-or-many	unspecified	AnyResource	Either	<code>foaf:Agent</code>	Agents who are responsible authorizing and/or has authorized effort to be expended to address a set of child change requests.
<code>oslc_cm:blocksTestExecutionRecord</code>	Zero-or-many	unspecified	Resource	Reference	<code>oslc_config:ChangeSet</code>	Associated QM resource that is blocked by this Change Request. It is likely that the target resource will be an <code>oslc_qm:TestExecutionRecord</code> but that is not necessarily the case.
<code>oslc_cm:closed</code>	Zero-or-one	unspecified	boolean	N/A	Unspecified	Whether or not the Change Request is completely done, no further fixes or fix verification is needed.
<code>oslc_cm:closeDate</code>	Zero-or-one	true	dateTime	N/A	Unspecified	The date at which no further activity or work is intended to be conducted.
<code>oslc_cm:fixed</code>	Zero-or-one	unspecified	boolean	N/A	Unspecified	Whether or not the Change Request has been fixed.
<code>oslc_cm:implementsRequirement</code>	Zero-or-many	unspecified	Resource	Reference	<code>oslc_rm:Requirement</code>	Implements associated Requirement. It is likely that the target resource will be an <code>oslc_rm:Requirement</code> but that is not necessarily the case.
<code>oslc_cm:inProgress</code>	Zero-or-one	unspecified	boolean	N/A	Unspecified	Whether or not the Change Request in a state indicating that active work is occurring. If <code>oslc_cm:inProgress</code> is true, then <code>oslc_cm:fixed</code> and <code>oslc_cm:closed</code> must also be false.
<code>oslc_cm:parent</code>	Zero-or-many	unspecified	AnyResource	Either	<code>oslc_cm:ChangeRequest</code>	The related parent change requests of the subject change request. Establishes a parent/child relationship between change requests.



## Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_cm:priority</code>	Zero-or-many	unspecified	AnyResource	Either	<code>oslc_cm:Priority</code>	Priority of this change request.
<code>oslc_cm:relatedChangeRequest</code>	Zero-or-many	unspecified	Resource	Reference	Unspecified	This relationship is loosely coupled and has no specific meaning.
<code>oslc_cm:relatedTestCase</code>	Zero-or-many	unspecified	Resource	Reference	<code>oslc_config:ChangeSet</code>	Related QM test case resource. It is likely that the target resource will be an <code>oslc_qm:TestCase</code> but that is not necessarily the case.
<code>oslc_cm:relatedTestExecutionRecord</code>	Zero-or-many	unspecified	Resource	Reference	<code>oslc_config:ChangeSet</code>	Related to a QM test execution resource. It is likely that the target resource will be an <code>oslc_qm:TestExecutionRecord</code> but that is not necessarily the case.
<code>oslc_cm:relatedTestPlan</code>	Zero-or-many	unspecified	Resource	Reference	<code>oslc_config:ChangeSet</code>	Related QM test plan resource. It is likely that the target resource will be an <code>oslc_qm:TestPlan</code> but that is not necessarily the case.
<code>oslc_cm:relatedTestScript</code>	Zero-or-many	unspecified	Resource	Reference	<code>oslc_config:ChangeSet</code>	Related QM test script resource. It is likely that the target resource will be an <code>oslc_qm:TestScript</code> but that is not necessarily the case.
<code>oslc_cm:reviewed</code>	Zero-or-one	unspecified	boolean	N/A	Unspecified	Whether or not the Change Request has been reviewed.
<code>oslc_cm:state</code>	Zero-or-one	unspecified	unspecified	Either	<code>oslc_cm:State</code>	Used to indicate the state of the change request. This property is often read-only, but could be changed using OSLC Actions.
<code>oslc_cm:status</code>	Zero-or-one	unspecified	string	N/A	Unspecified	Used to indicate the status of the change request. This property is often read-only.
<code>oslc_cm:testedByTestCase</code>	Zero-or-many	unspecified	Resource	Reference	<code>oslc_config:ChangeSet</code>	Test case by which this change request is tested. It is likely that the target resource will be an <code>oslc_qm:TestCase</code> but that is not necessarily the case.
<code>oslc_cm:tracksChangeSet</code>	Zero-or-many	unspecified	Resource	Reference	<code>oslc_config:ChangeSet</code>	Tracks a resource that represents a set of changes on the resource.
<code>oslc_cm:verified</code>	Zero-or-one	unspecified	boolean	N/A	Unspecified	Whether or not the resolution or fix of the Change Request has been verified.
<code>oslc:discussedBy</code>	Zero-or-one	unspecified	AnyResource	Either	<code>oslc:Discussion</code>	A series of notes and comments about this change request.
<code>oslc:instanceShape</code>	Zero-or-many	unspecified	Resource	Reference	<code>oslc:ResourceShape</code>	Resource Shape that provides hints as to resource property value-types and allowed values.
<code>oslc:serviceProvider</code>	Zero-or-many	unspecified	Resource	Reference	<code>oslc:ServiceProvider</code>	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.

## Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc:shortTitle</code>	Zero-or-one	unspecified	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. <b>SHOULD</b> include only content that is valid inside an XHTML <span> element.
<code>rdf:type</code>	Zero-or-many	unspecified	Resource	Reference	Unspecified	The resource type URLs, at least one of which should be <code>oslc_cm:ChangeRequest</code> .

### 2.5 Resource: ReviewTask

- **Describes:** <http://open-services.net/ns/cm#ReviewTask>
- **Summary:** A request to make a changes and review the change.
- **Description:** A review task can be used to request and approve changes to requirements, test plans, test cases or other resources.

#### ReviewTask Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>dcterms:contributor</code>	Zero-or-many	unspecified	AnyResource	Either	<code>oslc:Any</code>	The person(s) who are responsible for the work needed to complete the change request (reference: Dublin Core). It is likely that the target resource will be a <code>foaf:Person</code> but that is not necessarily the case.
<code>dcterms:created</code>	Zero-or-one	true	dateTime	N/A	Unspecified	Timestamp of resource creation (reference: Dublin Core).
<code>dcterms:creator</code>	Zero-or-many	unspecified	AnyResource	Either	<code>oslc:Any</code>	Creator or creators of resource (reference: Dublin Core). It is likely that the target resource will be a <code>foaf:Person</code> but that is not necessarily the case.
<code>dcterms:description</code>	Zero-or-one	unspecified	XMLLiteral	N/A	Unspecified	Descriptive text (reference: Dublin Core) about resource represented as rich text in XHTML content. <b>SHOULD</b> include only content that is valid and suitable inside an XHTML <div> element.
<code>dcterms:identifier</code>	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Assigned by the service provider when a resource is created. Not intended for end-user display.
<code>dcterms:modified</code>	Zero-or-one	true	dateTime	N/A	Unspecified	Timestamp of latest resource modification (reference: Dublin Core).
<code>dcterms:subject</code>	Zero-or-many	unspecified	string	N/A	Unspecified	Tag or keyword for a resource. Each occurrence of a <code>dcterms:subject</code> property denotes an additional tag for the resource.
<code>dcterms:title</code>	Exactly-one	unspecified	XMLLiteral	N/A	Unspecified	Title (reference: Dublin Core) or often a single line summary of the resource represented as rich text in XHTML content. <b>SHOULD</b> include only content that is valid and suitable inside an XHTML <div> element.
<code>oslc_cm:affectedByDefect</code>	Zero-or-many	unspecified	Resource	Reference	<code>oslc_cm:Defect</code>	Change request is affected by a reported defect. It is likely that the target resource will be an <code>oslc_cm:Defect</code> but that is not necessarily the case.
<code>oslc_cm:affectsPlanItem</code>	Zero-or-many	unspecified	Resource	Reference	Unspecified	Change request affects plan item.

## Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_cm:affectsRequirement</code>	Zero-or-many	unspecified	Resource	Reference	<code>oslc_rm:Requirement</code>	Change request affecting a Requirement. It is likely that the target resource will be an <code>oslc_rm:Requirement</code> but that is not necessarily the case.
<code>oslc_cm:approved</code>	Zero-or-one	unspecified	boolean	N/A	Unspecified	Whether or not the Change Request has been approved.
<code>oslc_cm:authorizer</code>	Zero-or-many	unspecified	AnyResource	Either	<code>foaf:Agent</code>	Agents who are responsible authorizing and/or has authorized effort to be expended to address a set of child change requests.
<code>oslc_cm:closed</code>	Zero-or-one	unspecified	boolean	N/A	Unspecified	Whether or not the Change Request is completely done, no further fixes or fix verification is needed.
<code>oslc_cm:closeDate</code>	Zero-or-one	true	dateTime	N/A	Unspecified	The date at which no further activity or work is intended to be conducted.
<code>oslc_cm:fixed</code>	Zero-or-one	unspecified	boolean	N/A	Unspecified	Whether or not the Change Request has been fixed.
<code>oslc_cm:inProgress</code>	Zero-or-one	unspecified	boolean	N/A	Unspecified	Whether or not the Change Request in a state indicating that active work is occurring. If <code>oslc_cm:inProgress</code> is true, then <code>oslc_cm:fixed</code> and <code>oslc_cm:closed</code> must also be false.
<code>oslc_cm:parent</code>	Zero-or-many	unspecified	AnyResource	Either	<code>oslc_cm:ChangeRequest</code>	The related parent change requests of the subject change request. Establishes a parent/child relationship between change requests.
<code>oslc_cm:priority</code>	Zero-or-many	unspecified	AnyResource	Either	<code>oslc_cm:Priority</code>	Priority of this change request.
<code>oslc_cm:relatedChangeRequest</code>	Zero-or-many	unspecified	Resource	Reference	Unspecified	This relationship is loosely coupled and has no specific meaning.
<code>oslc_cm:reviewed</code>	Zero-or-one	unspecified	boolean	N/A	Unspecified	Whether or not the Change Request has been reviewed.
<code>oslc_cm:state</code>	Zero-or-one	unspecified	unspecified	Either	<code>oslc_cm:State</code>	Used to indicate the state of the change request. This property is often read-only, but could be changed using OSLC Actions.
<code>oslc_cm:status</code>	Zero-or-one	unspecified	string	N/A	Unspecified	Used to indicate the status of the change request. This property is often read-only.
<code>oslc_cm:tracksChangeSet</code>	Zero-or-many	unspecified	Resource	Reference	<code>oslc_config:ChangeSet</code>	Tracks a resource that represents a set of changes on the resource.
<code>oslc_cm:tracksRequirement</code>	Zero-or-many	unspecified	Resource	Reference	<code>oslc_rm:Requirement</code>	Tracks the associated Requirement or Requirement ChangeSet resources. It is likely that the target resource will be an <code>oslc_rm:Requirement</code> but that is not necessarily the case.
<code>oslc_cm:verified</code>	Zero-or-one	unspecified	boolean	N/A	Unspecified	Whether or not the resolution or fix of the Change Request has been verified.
<code>oslc:discussedBy</code>	Zero-or-one	unspecified	AnyResource	Either	<code>oslc:Discussion</code>	A series of notes and comments about this change request.
<code>oslc:instanceShape</code>	Zero-or-many	unspecified	Resource	Reference	<code>oslc:ResourceShape</code>	Resource Shape that provides hints as to resource property value-types and allowed values.

## Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc:serviceProvider</code>	Zero-or-many	unspecified	Resource	Reference	<code>oslc:ServiceProvider</code>	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
<code>oslc:shortTitle</code>	Zero-or-one	unspecified	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. <b>SHOULD</b> include only content that is valid inside an XHTML <code>&lt;span&gt;</code> element.
<code>rdf:type</code>	Zero-or-many	unspecified	Resource	Reference	Unspecified	The resource type URIs, at least one of which should be <code>oslc_cm:ChangeRequest</code> .

### 2.6 Resource: Task

- **Describes:** <http://open-services.net/ns/cm#Task>
- **Summary:** An executable and trackable activity.
- **Description:** Used to track assigned work that to be completed within a certain time.

#### Task Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>dcterms:contributor</code>	Zero-or-many	unspecified	AnyResource	Either	<code>oslc:Any</code>	The person(s) who are responsible for the work needed to complete the change request (reference: Dublin Core). It is likely that the target resource will be a <code>foaf:Person</code> but that is not necessarily the case.
<code>dcterms:created</code>	Zero-or-one	true	dateTime	N/A	Unspecified	Timestamp of resource creation (reference: Dublin Core).
<code>dcterms:creator</code>	Zero-or-many	unspecified	AnyResource	Either	<code>oslc:Any</code>	Creator or creators of resource (reference: Dublin Core). It is likely that the target resource will be a <code>foaf:Person</code> but that is not necessarily the case.
<code>dcterms:description</code>	Zero-or-one	unspecified	XMLLiteral	N/A	Unspecified	Descriptive text (reference: Dublin Core) about resource represented as rich text in XHTML content. <b>SHOULD</b> include only content that is valid and suitable inside an XHTML <code>&lt;div&gt;</code> element.
<code>dcterms:identifier</code>	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Assigned by the service provider when a resource is created. Not intended for end-user display.
<code>dcterms:modified</code>	Zero-or-one	true	dateTime	N/A	Unspecified	Timestamp of latest resource modification (reference: Dublin Core).
<code>dcterms:subject</code>	Zero-or-many	unspecified	string	N/A	Unspecified	Tag or keyword for a resource. Each occurrence of a <code>dcterms:subject</code> property denotes an additional tag for the resource.
<code>dcterms:title</code>	Exactly-one	unspecified	XMLLiteral	N/A	Unspecified	Title (reference: Dublin Core) or often a single line summary of the resource represented as rich text in XHTML content. <b>SHOULD</b> include only content that is valid and suitable inside an XHTML <code>&lt;div&gt;</code> element.
<code>oslc_cm:affectedByDefect</code>	Zero-or-many	unspecified	Resource	Reference	<code>oslc_cm:Defect</code>	Change request is affected by a reported defect. It is likely that the target resource will be an <code>oslc_cm:Defect</code> but that is not necessarily the case.

## Standards Track Work Product

Prefix Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_cm:affectsPlanItem</code>	Zero-or-many	unspecified	Resource	Reference	Unspecified	Change request affects plan item.
<code>oslc_cm:affectsRequirement</code>	Zero-or-many	unspecified	Resource	Reference	<code>oslc_rm:Requirement</code>	Change request affecting a Requirement. It is likely that the target resource will be an <code>oslc_rm:Requirement</code> but that is not necessarily the case.
<code>oslc_cm:approved</code>	Zero-or-one	unspecified	boolean	N/A	Unspecified	Whether or not the Change Request has been approved.
<code>oslc_cm:authorizer</code>	Zero-or-many	unspecified	AnyResource	Either	<code>foaf:Agent</code>	Agents who are responsible authorizing and/or has authorized effort to be expended to address a set of child change requests.
<code>oslc_cm:closed</code>	Zero-or-one	unspecified	boolean	N/A	Unspecified	Whether or not the Change Request is completely done, no further fixes or fix verification is needed.
<code>oslc_cm:closeDate</code>	Zero-or-one	true	dateTime	N/A	Unspecified	The date at which no further activity or work is intended to be conducted.
<code>oslc_cm:fixed</code>	Zero-or-one	unspecified	boolean	N/A	Unspecified	Whether or not the Change Request has been fixed.
<code>oslc_cm:inProgress</code>	Zero-or-one	unspecified	boolean	N/A	Unspecified	Whether or not the Change Request is in a state indicating that active work is occurring. If <code>oslc_cm:inProgress</code> is true, then <code>oslc_cm:fixed</code> and <code>oslc_cm:closed</code> must also be false.
<code>oslc_cm:parent</code>	Zero-or-many	unspecified	AnyResource	Either	<code>oslc_cm:ChangeRequest</code>	The related parent change requests of the subject change request. Establishes a parent/child relationship between change requests.
<code>oslc_cm:priority</code>	Zero-or-many	unspecified	AnyResource	Either	<code>oslc_cm:Priority</code>	Priority of this change request.
<code>oslc_cm:relatedChangeRequest</code>	Zero-or-many	unspecified	Resource	Reference	Unspecified	This relationship is loosely coupled and has no specific meaning.
<code>oslc_cm:reviewed</code>	Zero-or-one	unspecified	boolean	N/A	Unspecified	Whether or not the Change Request has been reviewed.
<code>oslc_cm:state</code>	Zero-or-one	unspecified	unspecified	Either	<code>oslc_cm:State</code>	Used to indicate the state of the change request. This property is often read-only, but could be changed using OSLC Actions.
<code>oslc_cm:status</code>	Zero-or-one	unspecified	string	N/A	Unspecified	Used to indicate the status of the change request. This property is often read-only.
<code>oslc_cm:tracksChangeSet</code>	Zero-or-many	unspecified	Resource	Reference	<code>oslc_config:ChangeSet</code>	Tracks a resource that represents a set of changes on the resource.
<code>oslc:discussedBy</code>	Zero-or-one	unspecified	AnyResource	Either	<code>oslc:Discussion</code>	A series of notes and comments about this change request.
<code>oslc:instanceShape</code>	Zero-or-many	unspecified	Resource	Reference	<code>oslc:ResourceShape</code>	Resource Shape that provides hints as to resource property value-types and allowed values.
<code>oslc:serviceProvider</code>	Zero-or-many	unspecified	Resource	Reference	<code>oslc:ServiceProvider</code>	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.

## Standards Track Work Product

<i>Prefixed Name</i>	<i>Occurs</i>	<i>Read-only</i>	<i>Value-type</i>	<i>Representation</i>	<i>Range</i>	<i>Description</i>
<code>oslc:shortTitle</code>	Zero-or-one	unspecified	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. <b>SHOULD</b> include only content that is valid inside an XHTML <span> element.
<code>rdf:type</code>	Zero-or-many	unspecified	Resource	Reference	Unspecified	The resource type URIs, at least one of which should be <code>oslc_cm:ChangeRequest</code> .

### 3. Conformance

Change Management servers **MUST** follow the constraints defined here where required, and with the meanings defined here.

Change Management servers **MAY** provide additional constraints for specific purposes.